



IRON STRONG

**DUCTILE IRON PIPE
DIMENSIONS AND
WEIGHTS FOR SPECIAL
CLASSES OF PUSH-ON
JOINT DUCTILE IRON PIPE**

PIPE SIZE IN.	THICKNESS CLASS	NOMINAL THICKNESS IN.	OD* IN.	WT. OF BARREL PER FT. † LB.	TYTON® JOINT		
					WT. OF BELL LB.	WT. PER LGTH. † LB.	AVG. WT. PER FT. ‡ LB.
3	52	0.28	3.96	9.9	7	185	10.3
3	54	0.34	3.96	11.8	7	220	12.2
3	56	0.40	3.96	13.7	7	255	14.1
4	51	0.26	4.80	11.3	9	210	11.8
4	52	0.29	4.80	12.6	9	235	13.1
4	53	0.32	4.80	13.8	9	255	14.3
4	54	0.35	4.80	15	9	280	15.5
4	56	0.41	4.80	17.3	9	320	17.8
6	50	0.25	6.90	16	11	300	16.6
6	51	0.28	6.90	17.8	11	330	18.4
6	52	0.31	6.90	19.6	11	365	20.2
6	53	0.34	6.90	21.4	11	395	22.0
6	54	0.37	6.90	23.2	11	430	23.8
6	55	0.40	6.90	25	11	460	25.6
6	56	0.43	6.90	26.7	11	490	27.3
8	50	0.27	9.05	22.8	17	425	23.7
8	51	0.30	9.05	25.2	17	470	26.1
8	52	0.33	9.05	27.7	17	515	28.6
8	53	0.36	9.05	30.1	17	560	31.0
8	54	0.39	9.05	32.5	17	600	33.4
8	55	0.42	9.05	34.8	17	645	35.7
8	56	0.45	9.05	37.2	17	685	38.1
10	50	0.29	11.10	30.1	24	565	31.4
10	51	0.32	11.10	33.2	24	620	34.5
10	52	0.35	11.10	36.2	24	675	37.5
10	53	0.38	11.10	39.2	24	730	40.5
10	54	0.41	11.10	42.1	24	780	43.4
10	55	0.44	11.10	45.1	24	835	46.4
10	56	0.47	11.10	48	24	890	49.3
12	50	0.31	13.20	38.4	29	720	40.0
12	51	0.34	13.20	42	29	785	43.6
12	52	0.37	13.20	45.6	29	850	47.2
12	53	0.40	13.20	49.2	29	915	50.8
12	54	0.43	13.20	52.8	29	980	54.4
12	55	0.46	13.20	56.3	29	1040	57.9
12	56	0.49	13.20	59.9	29	1105	61.5
14	50	0.33	15.30	47.5	45	900	50.0
14	51	0.36	15.30	51.7	45	975	54.2
14	52	0.39	15.30	55.9	45	1050	58.4
14	53	0.42	15.30	60.1	45	1125	62.6
14	54	0.45	15.30	64.2	45	1200	66.7
14	55	0.48	15.30	68.4	45	1275	70.9
14	56	0.51	15.30	72.5	45	1350	75.0

CONTINUED ON REVERSE SIDE...

16	50	0.34	17.40	55.8	54	1060	58.8
16	51	0.37	17.40	60.6	54	1145	63.6
16	52	0.40	17.40	65.4	54	1230	68.4
16	53	0.43	17.40	70.1	54	1315	73.1
16	54	0.46	17.40	74.9	54	1400	77.9
16	55	0.49	17.40	79.7	54	1490	82.7
16	56	0.52	17.40	84.4	54	1575	87.4
18	50	0.35	19.50	64.4	59	1220	67.7
18	51	0.38	19.50	69.8	59	1315	73.1
18	52	0.41	19.50	75.2	59	1415	78.5
18	53	0.44	19.50	80.6	59	1510	83.9
18	54	0.47	19.50	86	59	1605	89.3
18	55	0.50	19.50	91.3	59	1700	94.6
18	56	0.53	19.50	96.7	59	1800	100.0
20	50	0.36	21.60	73.5	74	1395	77.6
20	51	0.39	21.60	79.5	74	1505	83.6
20	52	0.42	21.60	85.5	74	1615	89.6
20	53	0.45	21.60	91.5	74	1720	95.6
20	54	0.48	21.60	97.5	74	1830	101.6
20	55	0.51	21.60	103.4	74	1935	107.5
20	56	0.54	21.60	109.3	74	2040	113.4
24	50	0.38	25.80	92.9	95	1765	98.2
24	51	0.41	25.80	100.1	95	1895	105.4
24	52	0.44	25.80	107.3	95	2025	112.6
24	53	0.47	25.80	114.4	95	2155	119.7
24	54	0.50	25.80	121.6	95	2385	126.9
24	55	0.53	25.80	128.8	95	2415	134.1
24	56	0.56	25.80	135.9	95	2540	141.2
30	50	0.39	32.00	118.5	139	2270	126.2
30	51	0.43	32.00	130.5	139	2490	138.2
30	52	0.47	32.00	142.5	139	2705	150.2
30	53	0.51	32.00	154.4	139	2920	162.1
30	54	0.55	32.00	166.3	139	3130	174.0
30	55	0.59	32.00	178.2	139	3345	185.9
30	56	0.63	32.00	190.0	139	3560	197.7
36	50	0.43	38.30	156.5	184	3000	166.7
36	51	0.48	38.30	174.5	184	3325	184.7
36	52	0.53	38.30	192.4	184	3645	202.6
36	53	0.58	38.30	210.3	184	3970	220.5
36	54	0.63	38.30	228.1	184	4290	238.3
36	55	0.68	38.30	245.9	184	4610	256.1
36	56	0.73	38.30	263.7	184	4930	273.9

† Including bell; calculated weight of pipe rounded off to the nearest 5 lb.

‡ Including bell; average weight per foot, based on calculated weight of pipe before rounding.

*Tolerances of OD of spigot end; 3-12 in. ±0.06 in., 14-24 in. +0.05 in., -0.08 in., 30-36 in. +0.08 in., -0.06 in.



POCKET ENGINEER

Available for iOS + Android
or online at pe.mcwane.com

CONNECT WITH US ON



mcwaneductile.com

NEW JERSEY

183 Sitgreaves St.
Phillipsburg, NJ 08865
908-454-1161

OHIO

2266 S. 6th St.
Coshocton, OH 43812
740-622-6651

UTAH

1401 E. 2000 South
Provo, UT 84606
801-373-6910



canadapipe.com

CANADA

Suite 1 Frid St.
Hamilton, Ontario, Canada
L8P 4M3
905-547-3251

Rev. April 2022